

CARBICOTE™
STRIPPABLE COATINGS

SPRAY BOOTH COATINGS



CARBICOTE SPRAY BOOTH COATINGS

are applied to walls, ceilings, lights and floors in paint spray booths. After application the coating is periodically peeled off to remove the hazardous accumulation of paint overspray and then a new coat is applied.

- **942 PREMIUM WHITE STRIPPABLE**
White, Water-Base, Walls & Ceilings
- **945 ALL SURFACE CLEAR STRIPPABLE**
Clear, Water-Base, Walls, Ceiling, Lights
- **949 STANDARD BOOTH STRIPPABLE**
White, Water-Base, Walls & Ceilings

ASK ABOUT OUR OTHER SPECIALTY STRIPPABLE COATINGS FOR FLOORS AND OLD PAINTED BOOTHS.

Carbit Paint Company, LLC.
927 Blackhawk St., Chicago, IL 60642
312-280-2300

www.carbit.com
email: info@carbit.com

CARBIT®
COATING SOLUTIONS

Manufacturer of coatings in Chicago since 1925



387 Series Waterbase

SPEED DRY
ACRYLIC
ENAMEL

Direct-to-metal & Fade resistant

Non-flammable & Low VOC

Fast Drying & Early Moisture
Resistance

Stocked Colors & Made-To-Order

MANUFACTURER OF COATINGS IN CHICAGO SINCE 1925

Carbit is a third generation family owned and operated coating manufacturer. Whether it is custom manufacturing, application assistance, or environmental regulation support, Carbit's team of professionals provide timely "coating solutions" for the industrial and commercial marketplace.

387 Acrylic Stock & Made-to-Or-

Carbit stocks 387 in popular colors and will modify the color, gloss and viscosity on a Made-To-Order basis for 25 gallon minimum orders.

Made-to-order adjustments include:

- Viscosity range 70 - 95 KU
- Gloss range (60°) 20 - 80 units
- Any color and clear



Carbit uses dry pigments added in the factory to give you maximum coverage and fade resistance.

387 SERIES WATERBASE Speed Dry Acrylic Enamel



Speed Dry Acrylic can be applied directly to hot or cold rolled steel, galvanized metal, aluminum, concrete, and fiberglass. A primer is recommended when exposed to frequently wet or marine environments.

Dry-to-touch	30 minutes
Dry-to-recoat	1 hour
Dry-to-handle	1 hours

Flash Point	>212° F
VOC	<100 g/l

Please refer to the Product Data Sheet and MSDS for more information which can be found at www.carbit.com or call 1/312-2800-2300

PREPAINT CLEANER 707K3



Apply by hand, garden sprayer, or pressure washer.

Removes oils, oxidized paints, smoke and soot.

Concentrated: 1 gal. makes 10 or more gallons.

707K3 PREPAINT CLEANER is a highly concentrated, water based cleaner and degreaser. It cleans steel, aluminum, plastics and oxidized paints prior to painting with water or solvent based coatings. (Use Carbit Clean and Etch for galvanized metal.)

- **Safe** - non-flammable, low odor, biodegradable, no VOC.
- **Versatile** - removes mill and form oil, oxidized paint, smoke and soot.
- **Effective** - suspends oil and contaminant into cleaning solution for easy removal.

Effective Cleaning = Energy (scrubbing, water pressure,) + **Chemical** (soap, solvent) + **Temperature**

The goal is to find the best economic balance between the three factors.

SPRAY GUN PAINT 707K2 STRIPPER



NEW Product
water based
non-flammable

SGS™ is a blend of environmentally friendly, water based solvents and surfactants. It is used to safely remove industrial coatings from spray tips, paint guns, conveyor hooks and metal parts.

- **Safe** - nonflammable, non-caustic, water soluble, low odor and safe for all types of metal.
- **Environmentally Friendly** - biodegradable, pH neutral, and very low VOC.
- **Economical** - The solution can be used repeatedly and long lasting.

SGS™ (707K2) works by soaking into the paint and softening from the bottom up. Soaking time depends on the type of paint being removed, its thickness, and its age. Single component paints require 30 to 60 minutes soaking time. Two component paints may require 4 to 8 hours.